

# Space Pro

formerly View Plus for Business



The most comprehensive indoor air quality monitor in the Airthings for Business solution, including PM, noise and more. The Space Pro has an ultra low battery consumption customizable display. Can be seamlessly added into an existing Airthings for Business solution.

## PACKAGE CONTENT

Airthings Space Pro  
 6 x Lithium AA batteries  
 Double-sided tape  
 Security mount  
 Optional USB cable 6 ft. (1.8 m) (5 pack)  
 Optional bracket for fixed power supply  
 Optional in-wall fixed power supply

## REQUIREMENTS

Weight: 12.7 oz (360 g) with batteries  
 Dimensions: 6.69 x 3.54 x 1.30 in  
 (170 x 90 x 33 mm)  
 Airthings Space Hub needed to post  
 sensor values to cloud

## PRODUCT CODES

Device serial number: 2969xxxxxx  
 US / CANADA EAN: 7090031109615  
 SKU: 961 Model: 2969

## MOUNTING

Supports wall mounting or placement on table. Optimum product placement is breathing height of 3 - 6 ft (110 - 170 cm) above floor. Only suitable for mounting at heights below 6.56 ft (200 cm). Double-sided tape for wall mount included in package. Alternatively use 3 screws of type countersunk M4 (not included).

## PACKAGE

Dimensions: 7.9 x 4.5 x 2.4 in  
 (200 x 115 x 60 mm)  
 Weight: 15.17 oz (430 g)

## PRODUCT FEATURES

Sensors: PM<sub>1</sub>, PM<sub>2.5</sub>, VOC, CO<sub>2</sub>,  
 Noise, Relative Humidity, Air Pressure,  
 Temperature, Relative Light Intensity  
 (0 - 100 %)  
 Battery life: Up to 4 years on Lithium  
 (depending on the sensor interval settings)

## PRODUCT SPECIFICATIONS

Operational Environment (Temperature, Relative Humidity):  
 39 °F to 104 °F (4 °C to 40 °C) / 10 - 80 % (non-condensing)  
 Operation in temperatures < 32 °F (0 °C) or relative humidity > 90 % can cause  
 permanent damage to the products  
 Firmware updates are automatically downloaded and installed over the air (OTA)  
 via the Airthings Space Hub  
 SmartLink frequencies: 865-868/902-928 MHz depending on region


 PM<sub>1</sub>

 PM<sub>2.5</sub>

 CO<sub>2</sub>


VOC



HUMIDITY



TEMP



PRESSURE



LIGHT



NOISE


 VIRTUAL  
 SENSORS


OCCUPANCY



VIRUS RISK

# Space Pro

## SENSOR SPECIFICATIONS

Sensor sampling interval: 5 min.

Space Pro offers in addition configurable sensor sampling intervals from 2.5 min to 60 min for selected sensors.

Technology for Temperature, Humidity and Pressure Sensors:

### RELATIVE HUMIDITY SENSOR

Technology: Solid state sensor

Resolution: 0.5 %RH

Accuracy:  $\pm 3$  %RH at 77 °F (25 °C)

within 20-80 %RH

### TEMPERATURE SENSOR

Technology: Solid state sensor

Resolution: 0.1 °F (0.1 °C)

Accuracy:  $\pm 0.9$  °F at 77 °F /  $\pm 1.8$  °F

from 32-140°F ( $\pm 0.5$  °C at 25 °C /  $\pm 1$  °C from 0-60 °C)

### PRESSURE SENSOR

Technology: Solid state sensor

Pressure Accuracy:  $\pm 0.6$  mBar/hPA

(0.02 inHg) range 500-1100 mBar/hPA

### VOC SENSOR

Technology: Metal-oxide based gas sensor

Measurement range: 0-10 000 ppb

Settling time: ~7 days

Accuracy:  $20 \mu\text{g}/\text{m}^3 + 20\%$  of reading at values between 150 and  $2000 \mu\text{g}/\text{m}^3$

### PARTICULATE MATTER PM<sub>1</sub> AND PM<sub>2.5</sub>

Technology: laser scattering based optical particle counter

Particle size detection range:

300 nm to 10  $\mu\text{m}$

Measurement Range: 1-1000  $\mu\text{g}/\text{m}^3$

Measurement Accuracy: below  $150 \mu\text{g}/\text{m}^3$ :

$\pm (5 \mu\text{g}/\text{m}^3 + 15 \%)$ , above  $150 \mu\text{g}/\text{m}^3$ :  $\pm$

$(5 \mu\text{g}/\text{m}^3 + 20 \%)$ . Calibrated with a GRIMM

reference instrument using cigarette

smoke source.

Resolution: 1  $\mu\text{g}/\text{m}^3$

Classified as Class 1 Laser per

IEC60825-1 Ed. 3. This device complies

with 21 CFR 1040.10 and 1040.11, except

for conformance with IEC 60825-1 Ed. 3.,

as described in Laser Notice No. 56, dated

May 8, 2019. Caution: This device

contains one or more lasers. Use other

than as described in the user guide,

repair, or disassembly may cause damage,

which could result in hazardous exposure

to infrared.

### CO<sub>2</sub> SENSOR

NDIR Sensor (Non-Dispersive Infra-Red):

Measurement range 400-5000 ppm.

Settling time: ~7 days

Accuracy  $\pm 50$  ppm  $\pm 5 \%$  at 400-2000 ppm

within 50 - 95 °F (10 - 35 °C) and 0 - 80

%RH, after initial settling time of 7 days.

Resolution: 1 ppm

### LIGHT SENSOR

Measurement range: 0 - 100 %

### NOISE SENSOR

Dynamic range: 35 - 120 dBA SPL

(optimization pending)

### VIRUS RISK

Virtual sensor

## RADIO SPECIFICATIONS

### BLUETOOTH LOW ENERGY

Output power: <5 mW

Frequency Range (MHz):

2400.0 - 2483.5

### AIRTHINGS SMARTLINK

Output power: <25 mW

Frequency range (MHz):

North America 902-928

## PRODUCT DIMENSIONS

